

DEFY STAIN BLOCKER FOR ROOFS

PRODUCT DATA

DEFY Stain Blocker for Roofs

MANUFACTURER: SaverSystems

Richmond, IN 47374

800-860-6327

Fax 765-935-4999

www.saversystems.com

DESCRIPTION

DEFY Stain Blocker For Roofs is a milky white liquid treatment that dries to a clear natural look. Spray on cleaned asphalt shingle roofs to form an invisible barrier that blocks the return of unsightly roof stains. Stains are effectively blocked from returning for up to three years depending on roof conditions and climate. Maintenance coats of stain blocker can be re-applied every 2-3 years or at the first sign of stain return to help block further staining. DEFY Stain Blocker For Roofs contains no acids, caustics, or bleaches and will not harm plants when used as directed.

USES

DEFY Stain Blocker For Roofs is an effective way to block many stains from reoccurring. Helps maintain the appearance of recently cleaned asphalt roof shingles, tile roofs, cedar roofs, and more. Product is also effective on nearly any exterior painted or unpainted hard surface once stains have been removed.

BENEFITS

- Maintains appearance of roofs
- Long lasting
- Environmentally friendly
- Economical

DIRECTIONS FOR USE

ROOFS: DEFY Stain Blocker is ready to use. Do not dilute. Apply product to dry or slightly damp shingles using a low pressure pump up type garden sprayer. Use a course stream. Do not atomize. Apply uniformly to the point of saturation being careful not to over apply. A sign of over application is when it starts running down the roof. Start at the bottom of roof and work towards the peak in sections until entire roof has been treated. Dries in 1-8 hours depending on temperature and humidity.

OTHER SURFACES: DEFY Stain Blocker is also effective at blocking unsightly stains on concrete, brick, or painted surfaces. It can be applied to siding, driveways, sidewalks, patios and more. Apply one coat to saturation with a brush, roller or low pressure spray. When applying to horizontal surfaces, always limit application to a single coat and avoid "ponding", applying only as much product as the surface can easily absorb.

COVERAGE: Approximately 250 sq. ft. per gallon on roofs. 100 - 500 sq. ft. per gallon on other surfaces depending on texture and porosity.

CLEAN-UP: Rinse tools with water.

CAUTIONS

For exterior use only. Keep away from children. Can cause eye, skin, and mucus membrane irritation. Vapors and mist harmful. Use only with adequate ventilation. Avoid contact with eyes, skin, and inhalation of vapors. Wear protective gloves and eyewear. If vapors and mist are generated while applying, wear a NIOSHA/MSHA approved respirator. Use extreme caution when walking on wet roof surfaces during application. Surface will become slippery when wet or damp. Complete abidance of all OSHA roof safety and fall protection guidelines is recommended.

First Aid: In case of eye or skin contact, flush with water continuously for 15 minutes. If swallowed, drink large amount of water, do not induce vomiting. Get medical attention immediately in all cases of eye contact and ingestion, or if skin irritation persists. Consult Material Safety Data Sheet for additional health and safety information.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over field conditions and application, no guarantee as to the results is offered, expressed or implied. SaverSystems warrants this product to be free from defects. SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product has been applied. This warranty does not include the cost of labor for application.

SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

DEFY Stain Blocker For Roofs is available in 1 and 5 gallon recyclable plastic containers.

TRANSPORT AND STORAGE:

DEFY Stain Blocker For Roofs is not considered hazardous when under Department of Transportation (DOT) regulations. In case of spillage, absorb with inert material and dispose of in accordance with all applicable regulations. Do not stack pallets. Store in a cool, dry area. Keep from freezing.